

# Hybrid DVR



## Key Features

- Up to 16 ch @ 1080P
- Onvif
- HDD Up to 2 x Sata 6TB
- DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL

## Free DDNS

- Secured and Reliable Connectivity
- Remote Access Anywhere and Anytime
- No Need for Static IP

	Models	HDVR-430-4CH-26T-2-A HDVR-430-4CH-26T-2-B	HDVR-430-8CH-26T-2-A HDVR-430-8CH-26T-2-B	HDVR-430-16CH-26T-2-C
System	OS	Embedded Linux		
Video	Output	VGA, HDMI		
	Preview	4*AHD/TVI/CVI-1080P@25fps	8*1080P@25fps	16*1080P@25fps
	Recode	4*AHD/TVI/CVI-1080P@25fps	8*1080P@12fps	16*1080P @12fps
	Motion Detect	Each view window can set 192 (16*12) detection area,can set multi-level sensitivity (only for local channel)		
	Multi-mode Input	AHD : 4*1080P ; 4*720P ; 4*960H Hybrid : 4*1080P (CVBS) +4*1080P (IP) NVR : 8*1080P+8*960P;4*3M;4*5M	AHD : 8*1080N ; 4*1080P Hybrid : 2*1080P (CVBS) +2*1080P (IP) ; 4*1080N (CVBS) + 4*960P (IP) NVR : 16*1080P;9*1080P;16*960P; 4*5M;	AHD : 16*1080N ; 8*1080N;16*960H; Hybrid : 8*1080N (CVBS) +8*960P (IP) NVR : 8*1080P+8*960P; 4*3M ;4*5M
Audio	Audio	G.711A		
	Intercom	Support		
Port	Video Input/Output	4 * BNC / 1 * VGA, 1 * HDMI (MAX: 1920*1080)	8 * BNC / 1 * VGA, 1 * HDMI	16 * BNC / 1 * VGA, 1 * HDMI
	Audio Input/Output	4 * RCA / 1 * RCA	4 * RCA (Max: 8 channels) / 1 * RCA	2 * RCA (Max: 6 channels) / 1 * RCA
	Alarm Output	Optional (Max: 4 channels) / Optional (can be 1 channel)		
	Network port	RJ45 10M/100M		
	PTZ Control	1 * RS485 Support multipal PTZ Contract		
	USB port	2 * USB Port		
	HDD Port	2 * SATA hdd ports (up to 6T for each one)		
Wireless Port	3G、WIFI(can be USB WIFI Dongle)			
Others	Power	1*HDD: 12V/2A 2*HDD: 12V/5A 1 *HDD with screen: 12V / 3A	1*HDD: 12V/2A 2*HDD: 12V/5A	2*HDD: 12V/5A 4 * HDD: 12V/6A
	Working temperature	0 °C - + 55 °C	0 °C - + 55 °C	0 °C - + 55 °C
	Size	171mm*78mm	200mm*78mm	235mm*90mm
	Weight	135g	196g	279g