

NVR






Key Features

- Up to 24 ch @ 5MP and 32 Ch @ 4MP
- Onvif
- HDD Up to 8 x Sata 6TB
- DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL

Free DDNS

- Secured and Reliable Connectivity
- Remote Access Anywhere and Anytime
- No Need for Static IP

								
	Model	NVR-80-4CH-16T-5M	NVR-80-8CH-16T-3M	NVR-80-16CH-26T-3M	NVR-80-32CH-46T-1080P	NVR-80-32CH-86T-1080P		
System	System	Embedded Linux						
Video	Video input	4ch 5M/4ch4M	4ch5M/8ch4M/ 4ch3M/16ch960P	8ch 5M/16ch4M/ 16ch3M	24ch5M/32ch4M/ 16ch1080P	24ch5M/32ch4M/ 16ch1080P		
	Playback	2ch 5M/4ch3M/ 4ch960P	2ch5M/4ch4M/4ch3M/ 4ch960P	4ch 5M/4ch4M/ 8ch3M	4ch5M/9ch4M/ 16ch1080P	4ch5M/9ch4M/ 16ch1080P		
	Decode	H.265/H.264						
Audio	Compression	G.711a						
	Intercom	Unsupport	Unsupport	Support	Support	Support		
Management	Record mode	Manual>Alarm>Motiondetection>Timing						
	Inquire mode	Inquire by Time/Calendar/Event/Channel						
Interface	HDMI output	1*HDMI (MAX:4K)						
	VGA output	1*VGA(MAX:1080P)						
	Ethernet port	1*RJ45 1*10/100Mbps Ethernet port			1*RJ45 1*10/100/1000Mbps Ethernet port			
	POE ports	N/A						
	Audio I/O	0/0	0/0	1/1	1/1	1/1		
	Alarm I/O	0/0	0/0	0/0	16/4	16/4		
	USB Port	2*USB2.0 ports			1*USB2.0 ports, 1*USB3.0 ports	2*USB2.0 ports, 1*USB3.0 ports		
HDD	1*SATA interface (Up to 8TB)			2 SATA interface* 6TB	4 SATA interface* 6TB	8 SATA interface* 8TB		
General	Temperature	0 °C - + 55 °C						
	Humidity	10% -90% RH						
	Power supply	12V/2A	12V/2A	12V/4A	12V/6A	ATX		