

PTZ-10-200-20X-TDN

SSG PTZ-10 Family



Specifications

Product ID	PTZ-10-200-20X-TDN
Previous Product ID	PTZ-200X-20XB
Product Family	Series PTZ-10
CAMERA	
Imager	1/3" (4MP), 1/3" (3MP), 1/2.7" (2MP)
Resolution (MPX)	4MP, 2592x1520, 3MP, 2048x1536, 2MP, 1080p (1920 x 1080), 720p (1280 x 720), D1 (704 x 576/704 x 480), CIF (352 x 288/352 x 240)
Optical Zoom (LZ)	30X, 20X, 10X
Iris	F1.6 ~F2.8
View of Angle	H : 51.8° (W) ~5.86° (T) V : 39.1° (W) ~4.4° (T)
Min. illumination	Color: 0.01 Lux \ B/W: 0 Lux
Day/Night Color (DN)	ICR/TDN
BLC	Auto
WB	Auto
S/N Ratio	>50dB
DOME	
Communications Protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP
Software Control	IE, CMS, Management Platform
Mobile View(optional)	Support Windows, Symbian, iPhone platform smartphone
Preset Points	128
Pattern Scan	4 groups
Guard Tours	4 groups
Guard Points	Max. 16 points, dwell time user selectable
Operating temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Pan and Tilt position display	Support
Auto Control IR LED	PWM
Support ambient light detection	IR illumination on 1-15 grades selectable;
LED	9pcs
IR distance	up to 60 meters
Support ambient light detection	IR illumination on 1-9 grades selectable;
Humidity	≤95% Non Condensing
Power	DC12V ≤4A
Consumption	< 25W
Lightning Protection	Transient voltage 6000V
Communication mode	RS485 (+/-)
Connection	Coaxial Cable
Size/Weight	2.5KG
Related validation	IP66,CE,FCC,RoHs

Key Features

- 4" Total Metal body construction, IP66 rate protection
- Upto 30x Optical Zoom
- HD-IP digital interface output
- PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factor
- IR distance 50M

MODEL DESCRIPTION CHART

PTZ - 10 - MPX - LZ - DN

MPX = Resolution

200	-2.0 MP
300	-3.0 MP
400	-4.0 MP

LZ = Optical Zoom

10X	-10 Times Zoom
20X	-20 Times Zoom
36X	-36 Times Zoom

DN = Day/Night Color

TN	-TDN True Day/Night
SL	-Starlight